



AG22/6

AG22/6
AG22/6SL



SPECIAL FEATURES

- The lightest model from the grinders range (5.1 kg)
- Ergonomic switch with self-start protection and convenient guard ensure maximum safety
- Restart protection prevents the tool from automatically restarting after a power cut
- Rotating rear handle for convenient use in cutting operations
- Soft start and starting current limitation ensures the safety of the operator
- Easy access to motor carbon brushes to inspect their condition or replace if necessary
- 4 meter power cable with rubber insulation enables the user to move freely
- High-performance motor designed for prolonged operation
- Spindle lock for simple replacement of disk
- Blocking protection (AG22/6SL), detects when the disc is jammed and shuts down the machine immediately

TECHNICAL DATA		AG22/6	AG22/6SL
Voltage	V	230	230
Frequency	Hz	50-60	50-60
Input power	W	2200	2200
No-load speed	min ⁻¹	6500	6500
Max. disc diameter	mm	230	230
Weight according EPTA-Procedure 01/2003	kg	5.10	5.10
Soft Start and starting current limitation		■	■
Blocking protection		-	■
Self-Start protection		-	■
Antivibration handles		-	■
Item No.		134180279	134180379
Standart equipment		Safety guard, additional handle, support washer, lock nut, lock nut spanner	



AG230/2200S1

AG230/2200S1
AG230/2400S1
AG230/2600S1



SPECIAL FEATURES

- High-performance and efficient motor designed for prolonged operation
- Ergonomic switch with self-start protection and convenient guard ensure maximum safety of angle grinder operation;
- Soft start and starting current limitation ensures the safety of the operator
- Easy access to motor carbon brushes to inspect their condition and replace if necessary
- 4 meter power cable with rubber insulation enables the user to move freely
- Spindle lock for simple replacement of disk

TECHNICAL DATA		AG230/2200S1	AG230/2400S1	AG230/2600S1
Input power	W	2200	2400	2600
Voltage / Frequency	V~Hz	230 ~ 50	230 ~ 50	230 ~ 50
No-load speed	min ⁻¹	6500	6500	6500
Max. disc diameter	mm	230	230	230
Spindle thread	ISO	M14	M14	M14
Weight according EPTA-Procedure 01/2003	kg	5.50	5.50	5.80
Soft start and starting current limitation		■	■	■
Blocking protection		■	■	■
Item No.		134180479	134180779	134190179
Standart equipment		Safety guard, additional handle, support washer, lock nut, lock nut spanner		