



DC10/14,4L2
DC13/14,4L2
DC13/18L2



SPECIAL FEATURES

- Ergonomic and light design with soft-grip handle
- 2-speed planetary gearbox offers powerful support for both drilling and screw driving applications
- Adjustable torque regulator for precise regulation of the fastener tightening force
- Ergonomic trigger with variable speed regulation
- 2 x Li-Ion batteries and fast charger (cell producer: Samsung)
- Automatic spindle lock when releasing the switch
- Strong, high quality, locking RÖHM chuck ensures reliability and easy change of tooling
- Bright LED-lighting of the working area
- Battery charge status indicator informing the user about remaining operation time before recharge
- Up to 65 Nm of high torque ensures drilling (up to 36 mm) and screw driving (up to 10 mm)

TECHNICAL DATA		DC10/14,4 L2	DC13/14,4 L2	DC13/18L2
Battery voltage	V	14.4	14.4	18
Battery capacity	Ah	1.5	1.5	2.6
Battery type		Li-Ion	Li-Ion	Li-Ion
Battery's full charging time	min	35	35	60
No load speed (1st / 2nd gear):	min ⁻¹	0-450/0-1450	0-350 / 0-1800	0-400 / 0-1900
Maximum torque	Nm	30	65	70
Torque settings	Nr.	25+1	25+1	25+2
Max. drilling diameter in wood	mm	20	36	36
Max. drilling diameter in steel	mm	10	13	13
Max. screw diameter (in wood)	mm	10	10	10
Chuck capacity	min./max.	0.8 - 10	1.5 - 13	1.5 - 13
Weight (with battery)	kg	1.50	1.60	1.90
Item No.		170250570	170250670	170250870
Standart equipment		2 x Li-Ion batteries 1.5 Ah or 2.6 Ah , fast charger, belt holder, plastic case.		



DC13/14,4IL2
DC13/18IL2



SPECIAL FEATURES

- 25 torque adjustments + 2 separate modes for drilling and impact drilling
- 2-speed planetary gearbox offers powerful support for both drilling and screw driving applications
- Ergonomic trigger with variable speed regulation
- 2 x Li-Ion batteries and fast charger (cell producer: Samsung)
- Strong, high quality, locking RÖHM chuck ensures reliability and easy change of tooling
- Bright LED-lighting of the working area
- Battery charge status indicator informing the user about remaining operation time Before recharge
- Up to 70 Nm of high torque ensures drilling (up to 36 mm) and screw driving (up to 10 mm)
- Additional handle for tight grip during operation with maximum load or Impact drilling

TECHNICAL DATA		DC 13/14,4IL2	DC 13/18IL2
Battery voltage	V	14.4	18
Battery capacity	Ah	1.5	2.6
Battery type		Li-Ion	Li-Ion
Battery's full charging time	min	35	60
No load speed (1st / 2nd gear):	min ⁻¹	0-350 / 0-1800	0-400 / 0-1900
Maximum torque	Nm	65	70
Torque settings	Nr.	25+1	25+2
Max. drilling diameter in wood	mm	36	36
Max. drilling diameter in steel	mm	13	13
Max. screw diameter (in wood)	mm	10	10
Chuck capacity	min./max.	1.5 - 13	1.5 - 13
Weight (with battery)	kg	1.70	2.00
Item No.		170250770	170250970
Standart equipment		2 x Li-Ion batteries 1.5 Ah or 2.6Ah , fast charger, belt holder, plastic case.	